

EDGER CONCRETE TROWELS

Dependable Concrete Trowels that you can count on in the toughest conditions. After you float and finish the floor you can then eliminate the laborious hand finishing required along the walls and around any columns. Available in 2 sizes ESI has taken a “back to the basics” approach with an edger that is simply designed but built to take the rough handling of a construction job site and equipment rental use. Both models feature heavy-duty gearboxes and rotating rings that allow the edger to glide smoothly along the wall.



EET-60H

24” (600mm) blade width that works right up against the wall. Use this model for small dimension floors, a perfect companion model to a 36” twin ride-on trowel. A convenient folding handle makes it easier to transport in smaller vehicles and saves space for storage.



EET-75H

For working on those larger projects, use as your 30” (750mm) diameter edger trowel on your larger floors. A rotating guard ring allows you to finish right up against the wall and will give you the smooth finish you require. A convenient folding handle makes it easier to transport in smaller vehicles and saves space for storage.

FEATURES & BENEFITS:



FOLDED HANDLE FOR TRANSPORTATION



ROTATING RING



HD CENTRIFUGAL CLUTCH



GEAR BOX SIGHT GAUGE

Technical Data

DESCRIPTION	EET60H	EET75H
DIMENSION-LxWxH - in (mm)	65 x 25 x 43 (1,650 x 630 x 1,100)	60 x 30 x 39 (1,520 x 750 x 990)
GUARD RING DIAMETER - in (mm)	24 (600)	30 (750)
OPERATING WEIGHT - lb (kg)	123 (56)	141 (64)
HANDLE TYPE	FOLDABLE (FULL-FOLD)	FOLDABLE (FULL-FOLD)
FINISHING BLADE SIZE - in (mm)	9 x 4.7 (230 x 120)	10.6 x 4.7 (270 x 120)
MAX. BLADE PITCH ANGLE(°)	14	14
BLADE OPERATING SPEED (rpm)	85-135	85-138
ENGINE OPTIONS	HONDA GX120@4.0KW(2.9HP)	HONDA GX160@5.5KW(4.0HP)



Equipment Synergy International
 101 Gannaway Drive , Suite # 3
 P.O. Box 997
 Jamestown, North Carolina 27282
 Phone: 866.648.7101
 Fax: 336.310.1177
 Email: sales@theESchoice.com
 www.theESchoice.com